

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

SECTION 1: Identification of the substance/mixture and of the company/undertaking




1.1.	Product identifier	
	Trade name:	BIOMOUNT DPX LOW
	Chemical name:	-
	Catalogue number:	BML-X**
1.2.	Relevant identified uses of the substance or mixture and uses advised against	
	Uses:	Low viscosity medium for permanent covering of microscope samples and mounting cover slips.
	Uses advised against:	Only the identified uses are advised.
	Reason why uses advised against:	The product is intended for use only as an <i>in vitro</i> diagnostic medical device, registered at the Agency for Medicinal Products and Medical Devices and there is no reason to use it for other purposes.
1.3.	Details of the supplier of the safety data sheet	
	Supplier:	BioGnost Ltd.
	Address:	Medjugorska 59, Zagreb
	Telephone number:	+385 1 2409997
	Telefax:	+385 1 2404039
	e-mail of competent person:	msds@biognost.hr
	National contact:	-
1.4.	Emergency telephone numbers	
	National Protection and Rescue Directorate:	112
	Medical information:	+385 1 2348 342
	Other information:	-

SECTION 2. Hazards identification

2.1.	Classification of the substance or mixture	
2.1.1.	Classification according to Regulation (EC) No 1272/2008 (CLP)	
	Hazard class and category code:	Hazard statement*:
	Flam. Liq. 3	H226
	Asp. Tox. 1	H304
	Acute Tox. 4	H312
	Acute Tox. 4	H332
	Eye Irr. 2	H319
	Repr. 1B	H360Df
	STOT RE 2	H373
2.1.2.	Additional information	
	-	

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

* For full text of Hazard- and EU Hazard-statements: see SECTION 16

2.2.	Label elements	
	Product identification:	BIOMOUNT DPX LOW
	Identification number:	-
	Authorisation number:	-
	Hazard pictograms:	<div style="display: flex; flex-direction: column; align-items: center;"> <div style="display: flex; align-items: center; margin-bottom: 10px;"> GHS02  </div> <div style="display: flex; align-items: center; margin-bottom: 10px;"> GHS07  </div> <div style="display: flex; align-items: center;"> GHS08  </div> </div>
	Signal word:	Danger
	Hazard statement:	<p>H226 Flammable liquid and vapor.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H312+H332 Harmful in contact with skin or if inhaled.</p> <p>H319 Causes serious eye irritation.</p> <p>H360Df May damage the unborn child. Suspected of damaging fertility.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p>
	Precautionary statements:	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P280 Wear protective gloves/protective clothing/eye/protection/face protection.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P302 + P352 IF ON SKIN: Wash with plenty of soap and water.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/attention.</p>

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Supplemental hazard information (EU):	-
2.3. Other hazards	
<p>Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.</p> <p>Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH) - DBP.</p>	

SECTION 3. Composition/information on ingredients

CAS/EC/ Index number	REACH Registration No	Weight % content (or range)	Identification name	Classification according to Regulation (EC) No 1272/2008 (CLP)
1330-20-7/ 215-535-7/ 601-022-00-9	01-2119488216-32-XXXX	80 - 85 %	xylene	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373
84-74-2/ 201-557-4/ 607-318-00-4	-	5 -8 %	dibutyl phthalate	Repr. 1B; H360Df Aquatic Acute 1; H400

SECTION 4. First aid measures

4.1.	Description of first aid measures	
	General notes:	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Immediately remove any clothing soiled by the product.
	Following inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
	Following skin contact:	Remove contaminated clothing. Immediately wash with plenty of water and soap and rinse thoroughly. If symptoms persist, consult a doctor.
	Following eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
	Following ingestion:	DO NOT induce vomiting. If symptoms persist, consult a doctor.
	Self-protection of the first aider	Avoid direct contact with the chemical; use appropriate protective equipment described in Section 8.
4.2.	Most important symptoms and effects, both acute and delayed	

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

	Following inhalation:	High concentration vapor inhalation may cause headache, dizziness, difficult breathing and unconsciousness.
	Following skin contact:	Causes skin irritation, redness, swelling. Prolonged or repeated contact causes defatting and dry skin.
	Following eye contact:	Vapors irritate eyes. Splashing may cause irritation and redness.
	Following ingestion:	Nausea, vomiting (danger of aspiration), diarrhoea. Aspiration may cause headache, vertigo, nausea, dazed feeling-unconsciousness/coma, possible hypothermia, reactions to the heart/circulatory system such as vasodilation (flush), hypotension, arrhythmia (possible ventricular fibrillation through cardiac sensitization), danger of central respiratory paralysis or of cardiac arrest; functional disturbance to the liver and kidneys and persistent disturbance to the CNS as sequelae.
4.3.	Indication of any immediate medical attention and special treatment needed	
	No further relevant information available.	

SECTION 5. Firefighting measures		
5.1.	Extinguishing media	
	Suitable extinguishing media:	CO ₂ , powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
	Unsuitable extinguishing media:	water with full jet
5.2.	Special hazards arising from the substance or mixture	
	Hazardous by products of fire:	Formation of toxic gases is possible during heating or in case of fire.
5.3.	Advice for firefighters	
	Use a self-contained open-circuit compressed air breathing apparatus and fireproof clothing.	
5.4.	Additional information	
	Collect contaminated firefighting water separately. Do not contaminate the environment with extinguishing media.	

SECTION 6. Accidental release measures		
6.1.	Personal precautions, protective equipment and emergency procedures	
6.1.1.	For non-emergency personnel	
	Protective equipment:	Use personal protective equipment (see Section 8). Keep unprotected persons away.
	Accident prevention methods:	Evacuate members of all non-essential personnel and those members without protective equipment. Do not breathe in vapor, ensure adequate ventilation and avoid contact with skin and eyes. Remove all sources of sparks and ignition. Do not smoke.
	Emergency procedures:	Mark the area using proper signs.

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

6.1.2.	For emergency responders:	
	Use protective equipment; in case of inadequate ventilation use adequate airways protective equipment (see Section 8).	
6.2.	Environmental precautions:	
	Do not dispose of in sewage, drainage system and waterways. In case of large spillage contact National Protection and Rescue Directorate (NPRD) on 112.	
6.3.	Methods and materials for containment and cleaning up	
6.3.1.	Bunding, covering of drains; capping procedures:	Sand or clay barriers.
6.3.2.	Cleaning up:	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place the waste material in tightly closed impermeable containers. Store the substance in well ventilated storage rooms until disposal. Submit for disposal to the legal persons authorized by the Ministry of Environmental and Nature Protection. After disposal of the products, wash the area and involved materials with water.
6.3.3.	Other information:	Do not use tools that may cause sparks.
6.4.	Reference to other sections	
	See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.	

SECTION 7. Handling and storage		
7.1.	Precautions for safe handling	
7.1.1.	Protection measures	
	Measures to prevent fire:	Use in well ventilated storage rooms. Keep away from sources of heat and ignition. Carry out measures for preventing static electricity.
	Measures to prevent aerosol and dust generation:	Secure proper ventilation.
	Measures to protect the environment:	Prevent spilling into the sewage system and waterways.
	Other measures:	-
7.1.2.	Advice on general occupational hygiene:	
	Do not eat, drink or smoke in the workspace. Thoroughly wash hands after work and before eating.	
7.2.	Conditions for safe storage, including any incompatibilities	
	Technical measures and storage conditions:	Keep in tightly closed and upright set containers in a well ventilated storage rooms, and away from sources of heat, sunlight, and other incompatible substances.

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

	Packaging materials:	Manufacturer's original packaging.
	Requirements for storage rooms and vessels:	Keep away from food and drink. Keep the containers tightly closed.
	Advices for storage equipment:	The storage must be made of hard material; floors must be resistant to chemicals. There must be no drain that directly leads into sewage system. Secure proper ventilation.
	Further information on storage conditions:	Do not place the unused material in the storage room and do not use empty containers for storing other chemicals. Do not store with incompatible materials (see Section 10).
7.3.	Specific end use(s)	
	Recommendations:	-
	Industrial sector specific solutions:	-

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Substance	CAS No	Occupational exposure limit values/short term values		Biological limit values
		ppm	mg/m ³	
Xylene (all isomers)	1330-20-7	50/100	221/442	-
Dibutyl phthalate	84-74-2	-/-	5/10	-

Substance:	-		
EC No:	-	CAS No:	-

DNEL

Industrial

Route of exposure:	Acute effect local	Acute effect systemic	Chronic effect Local	Chronic effect systemic
Oral	-	-	-	-
Inhalation	-	289 mg/m ³ (xylene)	-	77 mg/m ³ (xylene)
Dermal	-	-	-	180 mg/kg (xylene)

Critical physical parameters: solubility, flammability, corrosivity:	-
--	---

Consumer

Route of exposure:	Acute effect local	Acute effect systemic	Chronic effect local	Chronic effect systemic
Oral	-	-	-	-
Inhalation	-	174 mg/m ³ (xylene)	-	14,8 mg/m ³ (xylene)

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Dermal	-	-	-	180 mg/kg (xylene)
--------	---	---	---	--------------------

PNEC	
Environmental protection target	PNEC
Fresh water	0.327 mg/l (xylene)
Freshwater sediments	12.46 mg/kg (xylene)
Marine water	0.327 mg/l (xylene)
Marine sediments	12.46 mg/kg (xylene)
Food chain	0.327 mg/l (xylene)
Microorganisms in sewage treatment	6.58 mg/l (xylene)
Soil (agricultural)	2.31 mg/kg (xylene)
Air	No information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Substance/mixture related measures to prevent exposure during identified uses:	Use personal protective equipment. Do not eat, drink or smoke in the workspace.
Structural measures to prevent exposure:	No information available
Organisational measures to prevent exposure:	Organization of work in order to reduce other worker's influence during work process.
Technical measures to prevent exposure:	Secure proper workspace ventilation in order to keep concentration levels in air below permitted levels.

8.2.2. Personal protection equipment:

8.2.2.1. Eye and face protection:	Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU)
8.2.2.2. Skin protection	

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

	Hand protection:	<p>Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.</p> <p>Full contact:</p> <p style="padding-left: 40px;">Glove material: Viton Glove thickness: 0.7 mm Break through time: 480 min</p> <p>Splash contact:</p> <p style="padding-left: 40px;">Glove material: Nitrile rubber Glove thickness: 0.4 mm Break through time: 35 min</p>
	Other skin protection:	Complete suit protecting against chemicals, flame retardant antistatic protective clothing (EN 13688). The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
8.2.2.3.	Respiratory protection:	Where risk assessment shows air-purifying respirators are appropriate use type ABEK (EN 14387) respirator cartridges as a backup to engine protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as CEN (EU).
8.2.2.4.	Thermal hazards:	No information available
8.2.3.	Environmental exposure controls	
	Substance/mixture related measures to prevent exposure:	See Section 6
	Structural measures to prevent exposure:	Use modern equipment.
	Organisational measures to prevent exposure:	Adapt the work process to the required working conditions of the workplace.
	Technical measures to prevent exposure:	See Section 6

SECTION 9. Physical and chemical properties			
9.1. Information on basic physical and chemical properties			
		Value	Method
	Physical state:	liquid	No information available
	Color:	colorless	No information available
	Odour/odour threshold:	aromatic/no information available	No information available
	Melting point / freezing point:	No information available	No information available

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Boiling point or initial boiling point and boiling range:	No information available	No information available
Flammability:	No information available	No information available
Lower and upper explosion limit:	No information available	No information available
Flash point:	29 °C	No information available
Auto-ignition temperature:	No information available	No information available
Decomposition temperature:	No information available	No information available
pH:	No information available	No information available
Kinematic viscosity:	No information available	No information available
Solubility:	No information available	No information available
Partition coefficient n-octanol/water (log value):	No information available	No information available
Vapour pressure:	No information available	No information available
Density and/or relative density	Insoluble in water	No information available
Relative vapour density:	No information available	No information available
Particle characteristics:	No information available	No information available
9.2.	Other information	
	-	

SECTION 10.: Stability and reactivity

10.1.	Reactivity:	No relevant information available.
10.2.	Chemical stability:	The product is chemically stable under recommended storage conditions.
10.3.	Possibility of hazardous reactions:	No dangerous reactions known.
10.4.	Conditions to avoid:	Sources of heat, flames and sparks.
10.5.	Incompatible materials:	Strong oxidizing agents.
10.6.	Hazardous decomposition products:	Carbon monoxide.

SECTION 11. Toxicological information

11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008				
	Acute toxicity:				
Route of exposure:	Method	Species	Effective Dose LD ₅₀ /LC ₅₀ or ATE _{mixture}	Exposure time	Results
Oral:	No information available	rat	LD ₅₀	No information available	3.523 mg/kg (xylene) 6.279 mg/kg (DBP)

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Dermal:	No information available	rabbit	LD ₅₀	No information available	>1.700 mg/kg (xylene) > 21.000 mg/kg (DBP)
Inhalation:	No information available	rat	LC ₅₀	4 h	29.09 mg/l (xylene)

Specific target organ toxicity - single exposure (STOT-SE):

	Specific effects	Target organ	Note
Oral:	No information available	No information available	-
Dermal:	No information available	No information available	-
Inhalation:	No information available	Respiratory system	May cause respiratory irritation

Aspiration hazard: May cause respiratory irritation. May be fatal if swallowed and enters respiratory system.

Irritation and corrosion

	Exposure time	Species	Evaluation	Method	Note
Skin corrosion/irritation	24h	rabbit (xylene)	-	-	Causes skin irritation.
Serious eye damage/irritation	-	-	-	-	No information available

Sensitization

Skin sensitization:	No information available
Respiratory sensitization:	No information available

Symptoms related to physical, chemical, and toxicological properties

Oral exposure:	Nausea, vomiting (danger of aspiration), diarrhoea. Aspiration may cause headache, vertigo, nausea, dazed feeling-unconsciousness/coma, possible hypothermia, reactions to the heart/circulatory system such as vasodilation (flush), hypotension, arrhythmia (possible ventricular fibrillation through cardiac sensitization), danger of central respiratory paralysis or of cardiac arrest; functional disturbance to the liver and kidneys and persistent disturbance to the CNS as sequelae.
Dermal exposure:	Causes skin irritation, redness, swelling. Prolonged or repeated contact causes defatting and dry skin.
Inhalation exposure:	Vapor inhalation may cause nose and throat irritation followed by sore throat, cough, difficult breathing and suffocating. High concentration vapor inhalation may cause headache, malaise and fatigue, difficult breathing, chest tightness, coordination and CNS disorders.

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Eye exposure:	Vapors irritate eyes. Splashing may cause irritation and redness, lacrimation, pain, swelling, blurred vision, photophobia.
---------------	---

Repeated dose toxicity (subacute, subchronic, chronic)
--

	Dose	Exposure time	Species	Method	Evaluation	Note
Subacute oral	No information available	No information available	No information available	No information available	No information available	-
Subacute dermal	No information available	No information available	No information available	No information available	No information available	-
Subacute inhalation	No information available	No information available	No information available	No information available	No information available	-
Subchronic oral	No information available	No information available	No information available	No information available	No information available	-
Subchronic dermal	No information available	No information available	No information available	No information available	No information available	-
Subchronic inhalation	No information available	No information available	No information available	No information available	No information available	-
Chronic oral	No information available	No information available	No information available	No information available	No information available	-
Chronic dermal	No information available	No information available	No information available	No information available	No information available	-
Chronic inhalation	No information available	No information available	No information available	No information available	No information available	-

Specific target organ toxicity - repeated exposure (STOT-RE):

	Specific effects	Target organ	Note
Subacute oral	No information available	No information available	-
Subacute dermal	No information available	No information available	-
Subacute inhalation	No information available	No information available	-
Subchronic oral	No information available	No information available	-

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Subchronic dermal	No information available	No information available	-
Subchronic inhalation	No information available	No information available	-
Chronic oral	No information available	No information available	-
Chronic dermal	No information available	No information available	-
Chronic inhalation	No information available	Central nervous system, liver, kidney	May cause damage to organs.

CMR effects (carcinogenicity, mutagenicity, reproductive toxicity)	
Carcinogenicity:	No information available
Mutagenicity <i>in-vitro</i> :	No information available
Genotoxicity:	No information available
Mutagenicity <i>in-vivo</i> :	No information available
Germ cell mutagenicity:	No information available
Reproductive toxicity:	Presumed human reproductive toxicant (Dibutyl phthalate). Overexposure may cause reproductive disorder(s) based on tests with laboratory animals. (Dibutyl phthalate).
Summary of evaluation of the CMR properties:	No information available

11.2.	Information on other hazards:
11.2.1.	Endocrine disrupting properties:
	This substance/mixture contains components considered to have endocrinedisrupting properties affecting human health, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100. (DBP)
11.2.2.	Other informations:
	-

SECTION 12. Ecological information						
12.1.	Toxicity					
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Fish	LC ₅₀	96 hours	<i>Oncorhynchus mykiss</i> (rainbow trout)	No information available	2.60 mg/l (xylene) 0.48 mg/l (DBP)	-
Crustacea:	EC ₅₀	48 hours	<i>Daphnia magna</i>	No information available	0.96 mg/l (xylene) 2.99 mg/l (DBP)	-
Algae/aquatic plants:	IC ₅₀	72 hours	<i>Pseudokirchneriella subcapitata</i>	No information available	4.36 mg/l (xylene)	-
Other organisms:	-	-	-	-	-	-
Chronic (long-term) toxicity	Doza	Exposure time	Species	Method	Evaluation	Note
Fish	LC ₅₀	96 hours	<i>Oncorhynchus mykiss</i> (rainbow trout) (DBP)	NOEC – 99 d	0.1 mg/l (DBP)	-
Crustacea:	EC ₅₀	48 hours	<i>Daphnia magna</i> (DBP)	NOEC – 21 d	0.158 mg/l (DBP)	-
Algae/aquatic plants:	IC ₅₀	72 hours	No information available	No information available	No information available	-
Other organisms:	-	-	-	-	-	-

12.2. Persistence and degradability

Abiotic degradation

	Degradation half-lives	Method	Evaluation	Note
Marine water	No information available	No information available	No information available	-
Fresh water	No information available	No information available	No information available	-
Air	No information available	No information available	No information available	-
Soil	No information available	No information available	No information available	-

Biodegradation

% Degradation	Time (days)	Method	Evaluation	Note
-	No information available	No information available	No information available	-

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

12.3. Bioaccumulative potential						
Octanol-water partition coefficient (log Kow)						
Value	Concentration	pH	°C	Method	Evaluation	Note
-	No information available	-	-	No information available	No information available	-
Bioconcentration Factor (BCF)						
Value	Species	Method		Evaluation	Note	
-	-	No information available		-	-	
Chronic ecotoxicity						
Value	Dose	Exposure time	Species	Method	Evaluation	Note
Chronic toxicity on fish	LC ₅₀	No information available	No information available	No information available	No information available	-
Chronic toxicity on crustacea (Daphnia)	EC ₅₀	No information available	No information available	No information available	No information available	-
12.4. Mobility in soil						
Known or predicted distribution in environmental compartments:						
No information available						
Surface tension:						
Value	°C	Concentration	Method	Note		
No information available	No information available	No information available	No information available	No information available -		
Adsorption / desorption						
Transport	A/D coefficient Henry's constant	log Kow	Evaporation rate	Method	Note	

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Soil-Water	No information available	No information available	No information available	No information available	-
Water-Air	No information available	No information available	No information available	No information available	-
Soil-Air	No information available	No information available	No information available	No information available	-

12.5. Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6. Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

No adverse effects are expected.

SECTION 13. Disposal considerations

13.1. Waste processing methods

13.1.1. Product/Packaging disposal:

Submit for disposal to the legal person authorized by the Ministry of Environmental and Nature Protection.

13.1.2. Waste codes/waste designations according to Low:

Disposal must be made according to official regulations.

13.1.3. Waste treatment – relevant information

No information available

13.1.4. Sewage disposal – relevant information:

Waste must not be disposed of into the sewage system.

13.1.5. Other disposal recommendations:

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Do not dispose of the product's remains into the sewage system. Submit the remains to the collectors authorized by the ministry in charge. Do not dispose of the packaging into the sewage system. Submit the packaging to the collectors authorized by the ministry in charge. Do not dispose of in places where ignition may occur.

13.1.6. Relevant Community provisions:
 Disposal must be made according to official regulations.

SECTION 14. Transport information

Transporting/shipment by road (ADR)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by rail (RID)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by inland waterways (ADN)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by sea (IMDG)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

Transport in bulk condition in accordance with Annex II. of MARPOL 73/78 and IBC Codex:	-
Transporting/shipment by air (ICAO-TI/IATA-DGR)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Further information:	-

SECTION 15. Regulatory information	
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
	EU regulations
	Authorisation and/or restrictions on use
	Authorisations: -
	Restrictions: -
	Other EU regulations: <p>Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC;</p> <p>Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC;</p> <p>Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work;</p> <p>Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006;</p> <p>REACH Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII);</p>
	Information according 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

National legislation:	Chemicals Act, Regulation on classification, packaging and labeling of dangerous substances, Ordinance on occupational exposure limit values and on biological limit values, Regulation on categories, types and classification of waste with a waste catalog and list of hazardous waste, Ordinance on writing Material safety data sheet, Transport of Hazardous Substances Act
-----------------------	---

15.2.	Chemical safety assessment
	None

SECTION 16. Other information

16.1.	Indication of changes:	-
-------	------------------------	---

16.2.	Abbreviations and acronyms:	<p>ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)</p> <p>IMDG: International Maritime Code for Dangerous Goods</p> <p>IATA: International Air Transport Association</p> <p>GHS: Globally Harmonised System of Classification and Labelling of Chemicals</p> <p>EINECS: European Inventory of Existing Commercial Chemical Substances</p> <p>CAS: Chemical Abstracts Service (division of the American Chemical Society)</p> <p>DNEL: Derived No-Effect Level (UK REACH)</p> <p>LC50: Lethal concentration, 50 percent</p> <p>LD50: Lethal dose, 50 percent</p> <p>PBT: Persistent, Bioaccumulative and Toxic</p> <p>vPvB: very Persistent and very Bioaccumulative</p>
-------	-----------------------------	---

16.3.	Key literature references and source of data:	-
-------	---	---

16.4.	Classification and procedure used to derive the classification for mixture according to Regulation (EC) 1272/2008 (CLP)	
-------	---	--

Classification	Classification procedure
-	-

16.5.	Relevant H statements (number and full text)	
-------	--	--

H:	H226	Flammable liquid and vapor.
	H304	May be fatal if swallowed and enters airways.
	H312	Harmful in contact with skin.
	H332	Harmful if inhaled.
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H335	May cause respiratory irritation.
	H360Df	May damage the unborn child. Suspected of damaging fertility.
	H373	May cause damage to organs through prolonged or repeated exposure.
	H400	Very toxic to aquatic life.

16.6.	Training advice:	-
-------	------------------	---

Trade name:	BIOMOUNT DPX LOW				
Product code:	BML-X**	Date of compilation:	26 June 2024	Version:	5

16.7.	Further information:	<p>** "X" in the product code marks different volumes (different packaging of the product)</p> <p>We are not responsible for consequences in case of failure to comply with instructions for use or improper use of the product described in this material safety data sheet.</p>
-------	----------------------	---

ANNEX: Exposure scenario resulting to Chemical safety assessment	
-	