

Page 1 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

1.1.	Product identifier				
	Trade name:	BIOMOUI	NT		
	Chemical name:	-			
	Catalogue number:	BMT-X**			
1.2.	Relevant identified us	es of the sul	ostance or mixt	ture and uses advised against	
	Uses:		-	xylene-based medium for permanent covering of slides and mounting cover slips.	
	Uses advised against:		Only the ide	ntified uses are advised.	
	Reason why uses advised against:		The product is intended for use only as an <i>in vitro</i> diagnostic medical device, registered at the Agency for Medicinal Products and Medical Devices and there is no reason to use it for other purposes.		
1.3.	Details of the supplier	of the safet	ty data sheet		
	Supplier:		BioGnost Ltd.		
	Address:		Medjugorska 59, Zagreb		
	Telephone number:		+385 1 2409997		
	Telefax:		+385 1 2404039		
	e-mail of competent p	person:	msds@biognost.hr		
	National contact:	National contact:		-	
1.4.	Emergency telephone numbers				
	National Protection ar	nd Rescue D	irectorate:	112	
	Medical information:	Medical information:		+385 1 2348 342	
	Other information:			-	

SECTIO	SECTION 2. Hazards identification					
2.1.	Classification of the substance or mixture					
2.1.1.	Classification according to Regulation (EC) No 12	72/2008 (CLP)				
	Hazard class and category code:	Hazard statement*:				
	Flam. Liq. 3	H226				
	Asp. Tox. 1	H304				
	Acute Tox. 4	H312				
	Acute Tox. 4	H332				
	Eye Irr. 2	H319				
	STOT RE 2	H373				
2.1.2.	Additional information					
	-					
* For fu	ıll text of Hazard- and EU Hazard-statements: see S	ECTION 16				



Page 2 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

2.2		
2.2.	Label elements	RIGMOUNT
	Product identification:	BIOMOUNT
	Identification number:	-
	Authorisation number:	
	Hazard pictograms:	GHS02 GHS07
	Signal word:	Danger
	Hazard statement:	 H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H312+H332 Harmful in contact with skin or if inhaled. H319 Causes serious eye irritation. H373 May cause damage to organs through prolonged or repeated exposure.
	Precautionary statements:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/protective clothing/eye/protection/face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308+P313 IF exposed or concerned: Get medical advice/attention.
	Supplemetal hazard information (EU):	-
2.3.	Other hazards	



Page 3 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3. Composition/information on ingredients							
CAS/ EC/ Index number	REACH Registration No	Weight % content (or range)	Identification name	Classification according to Regulation (EC) No 1272/2008 (CLP)			
1330-20-7/ 215-535-7/ 601-022-00-9	01-2119488216-32- XXXX	60 - 65 %	xylene	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Acute Tox. 4, H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373			

SECTI	SECTION 4. First aid measures				
4.1.	Description of first aid measures				
	General notes:	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Immediately remove any clothing soiled by the product.			
	Following inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.			
	Following ski contact:	Remove contaminated clothing. Immediately wash with plenty of water and soap and rinse thoroughly. If symptoms persist, consult a doctor.			
	Following eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.			
	Following ingestion:	DO NOT induce vomiting. If symptoms persist, consult a doctor.			
	Self-protection of the first aider	Avoid direct contact with the chemical; use appropriate protective equipment described in Section 8.			
4.2.	Most important symptoms a	and effects, both acute and delayed			
	Following inhalation:	High concentration vapor inhalation may cause headache, dizziness, difficult breathing and unconsciousness.			
	Following skin contact:	Causes skin irritation, redness, swelling. Prolonged or repeated contact causes defatting and dry skin.			
	Following eye contact:	Vapors irritate eyes. Splashing may cause irritation and redness.			



Page 4 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

	Following ingestion:	Nausea, vomiting (danger of aspiration), diarrhoea. Aspiration may cause headache, vertigo, nausea, dazed feeling-unconsciousness/coma, possible hypothermia, reactions to the heart/circulatory system such as vasodilation (flush), hypotension, arrhythmia (possible ventricular fibrillation through cardiac sensitization), danger of central respiratory paralysis or of cardiac arrest; functional disturbance to the liver and kidneys and persistent disturbance to the CNS as sequelae.	
4.3.	Indication of any immediate medical attention and special treatment needed		
	No further relevant information available.		

SECTION	SECTION 5. Firefighting measures				
5.1.	Extinguishing media				
	Suitable extinguishing media:	CO ₂ , powder or water spray. Fight larger fires with water spray or alcohol resistant foam.			
	Unsuitable extinguishing media:	water with full jet			
5.2.	Special hazards arising from the substance or mixture				
	Hazardous by products of fire:	Formation of toxic gases is possible during heating or in case of fire.			
5.3.	Advice for firefighters				
	Use a self-contained open-circuit co	ompressed air breathing apparatus and fireproof clothing.			
5.4.	Additional information				
	Collect contaminated firefighting water separately. Do not contaminate the environment with extinguishing media.				

SECTIO	SECTION 6. Accidental release measures				
6.1.	Personal precautions, protective ec	quipment and emergency procedures			
6.1.1.	For non-emergency personnel				
	Protective equipment:	Use personal protective equipment (see Section 8). Keep unprotected persons away.			
	Accident prevention methods:	Evacuate members of all non-essential personnel and those members without protective equipment. Do not breathe in vapor, ensure adequate ventilation and avoid contact with skin and eyes. Remove all sources of sparks and ignition. Do not smoke.			
	Emergency procedures:	Mark the area using proper signs.			
6.1.2.	For emergency responders:				
	Use protective equipment; in case of inadequate ventilation use adequate airways protective equipment (see Section 8).				
6.2.	Environmental precautions:				



Page 5 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

	•	age, drainage system and waterways. In case of large spillage contact National irectorate (NPRD) on 112.
6.3.	Methods and materials for	or containment and cleaning up
6.3.1.	Bunding, covering of drains; capping procedures:	Sand or clay barriers.
6.3.2.	Cleaning up:	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place the waste material in tightly closed impermeable containers. Store the substance in well ventilated storage rooms until disposal. Submit for disposal to the legal persons authorized by the Ministry of Environmental and Nature Protection. After disposal of the products, wash the area and and involved materials with water.
6.3.3.	Other information:	Do not use tools that may cause sparks.
6.4.	Reference to other section	ons
	See Section 7 for informa	5
		ation on personal protection equipment.
	See Section 13 for dispos	sal information.

SECTIO	ON 7. Handling and storage		
7.1.	Precautions for safe handling		
7.1.1.	Protection measures		
	Measures to prevent fire:		Use in well ventilated storage rooms. Keep away from sources of heat and ignition. Carry out measures for preventing static electricity.
	Measures to prevent aerosol and dust generation:		Secure proper ventilation.
	Measures to protect the environment:		Prevent spilling into the sewage system and waterways.
	Other measures:		-
7.1.2.	Advice on general occupational hygiene:		
	Do not eat, drink or smoke in the workspace. Thor	oughly wa	ash hands after work and before eating.
7.2.	Conditions for safe storage, including any incompa	atibilities	
	Technical measures and storage conditions:	well ven	tightly closed and upright set containers in a stillated storage rooms, and away from sources sunlight, and other incompatible substances.
	Packaging materials:	Manufa	cturer's original packaging.
	Requirements for storage rooms and vessels:	Keep aw tightly c	vay from food and drink. Keep the containers closed.



Page 6 of 18

Trade name:		BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5	

	Advices for storage equipment:	The storage must be made of hard material; floors must be resistant to chemicals. There must be no drain that directly leads into sewage system. Secure proper ventilation.
	Further information on storage conditions:	Do not place the unused material in the storage room and do not use empty containers for storing other chemicals. Do not store with incompatible materials (see Section 10).
7.3.	Specific end use(s)	
	Recommendations:	-
	Industrial sector specific solutions:	-

SECTION 8. Expos		ois/persona	ii protec	uon			
8.1. Control pa	rameters						
Substance		CASI	CAS No		exposure limit term values	Biological limit values	
				ppm	mg/m³		
Xylene (all isomers)		1330-2	20-7	50/100	221/442	-	
Substance: -							
EC No: -		CAS No:	_				
DNEL							
				Industrial			
Doute of oversume	Acu	te effect	Ad	cute effect	Chronic e	ffect	Chronic effect
Route of exposure:		local	:	systemic	Local		systemic
Oral	-		-		-		-
Inhalation	-		289 mg	g/m³ (xylene)	-		77 mg/m³ (xylene)
Dermal	-		-		-		180 mg/kg (xylene)
Critical physical par	ameters:	solubility, fla	mmabilit	ty, corrosivity:	-		
				Consumer			
Route of exposure:		te effect local		cute effect systemic	Chronic e local	ffect	Chronic effect systemic
Oral	-		-		-		-
Inhalation	-		174 mg	g/m³ (xylene)	-		14,8 mg/m³ (xylene)
Dermal	-		-		-		180 mg/kg (xylene)
PNEC	•				•		
Environmental prot	ection tar	net		PNEC			



Page 7 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

Fresh water	0.327 mg/l (xylene)
Freshwater sediments	12.46 mg/kg (xylene)
Marine water	0.327 mg/l (xylene)
Marine sediments	12.46 mg/kg (xylene)
Food chain	0.327 mg/l (xylene)
Microorganisms in sewage treatment	6.58 mg/l (xylene)
Soil (agricultural)	2.31 mg/kg (xylene)
Air	No information available

8.2.	Exposure controls	
8.2.1.	Appropriate engineering control	5
	Substance/mixture related measures to prevent exposure during identified uses:	Use personal protective equipment. Do not eat, drink or smoke in the workspace.
	Structural measures to prevent exposure:	No information available
	Organisational measures to prevent exposure:	Organization of work in order to reduce other worker's influence during work process.
	Technical measures to prevent exposure:	Secure proper workspace ventilation in order to keep concentration levels in air below permitted levels.
8.2.2.	Personal protection equipment:	
8.2.2.1.	Eye and face protection:	Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU)
8.2.2.2.	Skin protection	
		Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.
	Hand protection:	Full contact: Glove material: Viton Glove thickness: 0.7 mm Break through time: 480 min
		Splash contact:
		Glove material: Nitrile rubber Glove thickness: 0.4 mm
		Break through time: 35 min



Page 8 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

	Other skin protection:	Complete suit protecting against chemicals, flame retardant antistatic protective clothing (EN 13688). The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
8.2.2.3.	Respiratory protection:	Where risk assessment shows air-purifying respirators are appropriate use type ABEK (EN 14387) respirator cartridges as a backup to engine protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as CEN (EU).
8.2.2.4.	Thermal hazards:	No information available
8.2.3.	Environmental exposure controls	
	Substance/mixture related measures to prevent exposure:	See Section 6
	Structural measures to prevent exposure:	Use modern equipment.
	Organisational measures to prevent exposure:	Adapt the work process to the required working conditions of the workplace.
	Technical measures to prevent exposure:	See Section 6

1.	Information on basic physical and chemic	al properties	
		Value	Method
	Physical state:	liquid	No information available
	Color:	light yellow	No information available
	Odour/odour threshold:	aromatic/no information available	No information available
	Melting point / freezing point:	No information available	No information available
	Boiling point or initial boiling point and boiling range:	No information available	No information available
	Flammability:	No information available	No information available
	Lower and upper explosion limit:	No information available	No information available
	Flash point:	29 °C	No information available
	Auto-ignition temperature:	No information available	No information available
	Decomposition temperature:	No information available	No information available
	рН:	No information available	No information available
	Kinematic viscosity:	No information available	No information available
	Solubility:	No information available	No information available



Page 9 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

	Partition coefficient n-octanol/water (log value):	No information available	No information available
	Vapour pressure:	No information available	No information available
	Density and/or relative density	Insoluble in water	No information available
	Relative vapour density:	No information available	No information available
	Particle characteristics:	No information available	No information available
9.2.	Other information		
	-		

SECTIO	SECTION 10.: Stability and reactivity				
10.1.	Reactivity:	No relevant information available.			
10.2.	Chemical stability:	The product is chemically stable under recommended storage conditions.			
10.3.	Possibility of hazardous reactions:	No dangerous reactions known.			
10.4.	Conditions to avoid:	Sources of heat, flames and sparks.			
10.5.	Incompatible materials:	Strong oxidizing agents.			
10.6.	Hazardous decomposition products:	Carbon monoxide.			

SECTION 11. T	oxicological information	on			
11.1. Inform	ation on hazard classes	as defined in	Regulation (EC	C) No 1272/2008	
Acute	toxicity:				
Route of exposure:	Method	Species	Effective Dose LD ₅₀ /LC ₅₀ or ATE _{mixture}	Exposure time	Results
Oral:	No information available	rat	LD ₅₀	No information available	3.523 mg/kg (xylene)
Dermal:	No information available	rabbit	LD ₅₀	No information available	>1.700 mg/kg (xylene)
Inhalation:	No information available	rat	LC ₅₀	4 h	29.09 mg/l (xylene)
Specifi	c target organ toxicity -	single expos	ure (STOT-SE):		
	Specif	Specific effects		Target organ	Note
Oral:	No information av	rmation available		nformation available	-
Dermal:	No information av	ailable	No ir	nformation available	-
Inhalation:	No information av	ailable	Respiratory system		May cause respiratory irritation



Page 10 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

Aspirat	Aspiration hazard:			May cause respiratory irritation. May be fatal if swallowed and enters respiratory system.				
Irritatio	n and c	orrosion						
			oosure ime	Species E	valuation	Method		Note
Skin corrosion/i	ritation	24h	rabl (xyle	oit ene)		-	Causes s	kin irritation.
Serious eye damage/irritatio	n	–	-	-		_	No infor	mation available
Sensitiz	zation							
Skin sensitizatio	n:	No informa	ation available					
Respiratory sensitization:		No informa	ation available)				
Oral exposure: Dermal exposure Inhalation exposure:	Na nai hea ver of the Cai dry Va bre and	Mausea, vomiting (danger of aspiration), diarrhoea. Aspiration may cause headache, vertigo nausea, dazed feeling-unconsciousness/coma, possible hypothermia, reactions to the heart/circulatory system such as vasodilation (flush), hypotension, arrhythmia (possible ventricular fibrillation through cardiac sensitization), danger of central respiratory paralysis of cardiac arrest; functional disturbance to the liver and kidneys and persistent disturbance the CNS as sequelae. Causes skin irritation, redness, swelling. Prolonged or repeated contact causes defatting and dry skin. Vapor inhalation may cause nose and throat irritation followed by sore throat, cough, difficult breathing and suffocating. High concentration vapor inhalation may cause headache, malais and fatigue, difficult breathing, chest tightness, coordination and CNS disorders.					ns to the (possible tory paralysis or it disturbance to s defatting and , cough, difficul adache, malaise ers.	
Eye exposure:		•	eyes. Splashin ohotophobia.	g may cause ir	ritation and	d redness, l	acrimation, p	pain, swelling,
Repeat	ed dose	toxicity (sub	acute, subchr	onic, chronic)				
, -		Dose	Exposure time	Species	Metho	d E	valuation	Note
Subacute oral	No i availa	information ble	No information available	No information available	No inform availab	ation i	lo nformation vailable	-
Subacute dermal	No i availa	information ble	No information available	No information available	No inform availab	ation i	lo nformation vailable	-



Page 11 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

			<u>I</u>			
Subacute inhalation	No information available	No information available	No information available	No information available	No informati available	on -
Subchronic oral	No information available	No information available	No information available	No information available	No informati available	on -
Subchronic dermal	No information available	No information available	No information available	No information available	No informati available	on -
Subchronic inhalation	No information available	No information available	No information available	No information available	No informati available	on -
Chronic oral	No information available	No information available	No information available	No information available	No informati available	on -
Chronic dermal	No information available	No information available	No information available	No information available	No informati available	on -
Chronic inhalation	No information available	No information available	No information available	No information available	No informati available	on -
	i	i	:	i	i	i
Specific	target organ toxic	city - repeated e	xposure (STO	Γ-RE):		
		Specific effects		Target organ		Note
Subacute oral		No information available		No information available		-
Subacute dermal		No information	available	No information available		_

Specific target organ toxicity - repeated exposure (STOT-RE):					
	Specific effects	Target organ	Note		
Subacute oral	No information available	No information available	-		
Subacute dermal	No information available	No information available	-		
Subacute inhalation	No information available	No information available	-		
Subchronic oral	No information available	No information available	-		
Subchronic dermal	No information available	No information available	-		
Subchronic inhalation	No information available	No information available	-		
Chronic oral	No information available	No information available	-		
Chronic dermal	No information available	No information available	-		
Chronic inhalation	No information available	Central nervous system, liver, kidney	May cause damage to organs		

CMR effects (carcinogenicity, mutagenicity, reproductive toxicity)		
Carcinogenicity:	No information available	
Mutagenicity in-vitro:	No information available	
Genotoxicity:	No information available	



Page 12 of 18

Trade name:	BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5

	Mutagenicity in-vivo:	No information available
	Germ cell mutagenicity:	No information available
	Reproductive toxicity:	No information available
	Summary of evaluation of the CMR properties:	No information available
11.2.	Information on other hazards:	
11.2.1.	Endocrine disrupting properties:	
	No known endocrine disrupting properthat affect human health.	erties
11.2.2.	Other informations:	
	-	

SECTION 12. Ecologi	ical inforn	nation				
12.1. Toxicity						
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish	LC ₅₀	96 hours	Oncorhynchus mykiss (rainbow trout)	No information available	2.60 mg/l (xylene)	-
Crustacea:	EC ₅₀	48 hours	Daphnia magna	No information available	0.96 mg/l (xylene)	-
Algae/aquatic plants:	IC ₅₀	72 hours	Pseudokirchneriella subcapitata	No information available	4.36 mg/l (xylene)	-
Other organisms:	-	-	-	-	-	-
Chronic (long-term) toxicity	Doza	Exposure time	Species	Method	Evaluation	Note
Fish	LC ₅₀	96 hours	No information available	No information available	No information available	-
Crustacea:	EC ₅₀	48 hours	No information available	No information available	No information available	-
Algae/aquatic plants:	IC ₅₀	72 hours	No information available	No information available	No information available	_



Page 13 of 18

Trade	name:					ВІО	МО	UNT		go	<u> </u>
Produ	ct code	:	BMM-X**		Date of co	ompilation:	21	Dec	2022	Version:	5
Other o	organisr	ns:			-			_		-	
12.2.	Persis	tence	e and degradab	ility							
	Abiot	ic de	gradation		:						:
			Degradation ha	lf-lives		Method			Eva	aluation	Note
Marine water		No	information ava	ailable	No inf	formation ava	ilabl	le	No informa	tion available	-
Fresh v	vater	No	information ava	ailable	No inf	formation ava	ilabl	le	No informa	tion available	-
Air		No	information ava	ailable	No inf	formation ava	ilabl	le	No informa	tion available	-
Soil		No	information ava	ailable	No inf	formation ava	ilabl	le	No informa	tion available	-
	1										
	Biode	grad	ation								
% Deg	% Degradation Time (days)			Method			Evaluation		No	te	
-			No inforr available	nation	No inforn available	nation		No info vailab	ormation le	-	
12.3.			ılative potentia								
			ater partition co								
Valu			ncentration	рН	°C	Method		Evaluation		N	ote
-			No information - available		-	No information available		n No informatio available		-	
	Bioco	ncen	tration Factor (BCF)							
\	/alue		Specie	es		Method		Εν	valuation	No	te
-			-		No infa	ormation ole	_			-	
	Chron	nic ec	otoxicity								
	Valu	e	Dos	e	Exposure time	Specie	S	N	Method	Evaluation	Note



Trade i	name	e:					BIO	MOUNT					
Product code: B		ВММ	BMM-X** Dat		Date of compilation: 21 Dec 2			2022	2022 Version:		5		
Chronic toxicity on fish LC ₅₀		No inform availal				ormation ailable	No informa		-				
Chronic toxicity on crustacea (Daphnia)		EC ₅₀	No inform availab		No No information in		ormation ailable	No informa availab		-			
12.4.	Kno [,] No i		predict		ribution in er	nvironme	ntal compa	artments:					
	Value °C Concentration			Method		Note							
	No avai	lable	informa	ation			No information available		No information available		-		
	Ads	-	n / desc D coeff										
Transpo	ort	-	nry's co		log Kow		Evaporation rate		Method		Note		
Soil-Wa	ater	No availa		rmatio	n No inf available	ormation	n No information available			No information available		-	
Water-	۹ir	No availa		rmatio	n No inf available	ormation	No information available			No information available		-	
Soil-Air No informati available		rmatio	on No information available		n No information available			No information available					
12.5.			PBT and		assessment								
12.6.	End	ocrine	disrupt	ing pro	perties								

SECTION 13. Disposal considerations

Other adverse effects

No adverse effects are expected.

13.1. Waste processing methods

12.7.



Page 15 of 18

Trade name:		BIOMOUNT					
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5		

13.1.1.	Product/Packaging dispo	osal:					
	Submit for disposal to th Protection.	e legal person authorized by the Ministry of Environmental and Nature					
13.1.2.	Waste codes/waste desig	nations according to Low:					
	Disposal must be made a	according to official regulations.					
13.1.3.	Waste tretment – relevan	nt information					
	No information available						
13.1.4.	Sewage disposal – releva	nt information:					
	Waste must not be dispo	sed of into the sewage system.					
13.1.5.	Other disposal recommendations:						
	Do not dispose of the product's remains into the sewage system. Submit the remains to the collectors authorized by the ministry in charge. Do not dispose of the packaging into the sewage system. Submit the packaging to the collectors authorized by the ministry in charge. Do not dispose of in places where ignition may occur.						
13.1.6.	Relevant Community provisions:						
	Disposal must be made a	ccording to official regulations.					
SECTIO	N 14. Transport information	on					
	Transporting/shipment by	road (ADR)					
UN num	ıber:	1307					
	ber: per shipping name:	1307 Xylenes					
UN prop							
UN prop	per shipping name: rt hazard class(es):	Xylenes					
UN prop Transpo Packing	per shipping name: rt hazard class(es):	Xylenes 3					
UN prop Transpo Packing Environr	per shipping name: rt hazard class(es): group:	Xylenes 3 III					
UN prop Transpo Packing Environr	per shipping name: rt hazard class(es): group: mental hazards:	Xylenes 3 III					
UN prop Transpo Packing Environr Special p	per shipping name: rt hazard class(es): group: mental hazards: precautions for user: Transporting/shipment by	Xylenes 3 III					
UN prop Transpo Packing Environr Special p UN num	per shipping name: rt hazard class(es): group: mental hazards: precautions for user: Transporting/shipment by	Xylenes 3 III rail (RID)					
UN prop Transpo Packing Environr Special p UN num UN prop	per shipping name: Int hazard class(es): Int group: Int	Xylenes 3 III rail (RID) 1307					



Page 16 of 18

Trade name:	BIOMOUNT					
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5	

Special precautions for user:	-
Transporting/shipment by inland	waterways (ADN)
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by sea (IN	MDG)
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transport in bulk condition in accordance with Annex II. of MARPOL 73/78 and IBC Codex:	-
Transporting/shipment by air (IC/	AO-TI/IATA-DGR)
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Further information:	

SECTIO	CTION 15. Regulatory information						
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture						
	EU regulations						
	Authorisation and/or restrictions on use						
	Authorisations: -						
	Restrictions: -						



Page 17 of 18

Trade name:		BIOMOUNT				
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5	

	Other EU regulations:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC; Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC; Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work; Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006; REACH Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII);
	Information according 1999 guideline)	/13/EC about limitation of emissions of volatile organic compounds (VOC-
	National legislation:	Chemicals Act, Regulation on classification, packaging and labeling of dangerous substances, Ordinance on occupational exposure limit values and on biological limit values, Regulation on categories, types and classification of waste with a waste catalog and list of hazardous waste, Ordinance on writing Material safety data sheet, Transport of Hazardous Substances Act
15.2.	Chemical safety assessment	
	None	

SECTIO	ON 16. Other information	
16.1.	Indication of changes:	-
16.2.	Abbreviations and acronyms:	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
16.3.	Key literature references and source of data:	-



Page 18 of 18

Trade name:		BIOMOUNT					
Product code:	BMM-X**	Date of compilation:	21 Dec 2022	Version:	5		

16.4.	Classification and procedure used to derive the classification for mixture according to Regulation (EC) 1272/2008 (CLP)		
Classification			Classification procedure
_			-
16.5.	Rele	evant H statements (nu	umber and full text)
		H226	Flammable liquid and vapor.
		H304	May be fatal if swallowed and enters airways.
	H:	H312	Harmful in contact with skin.
		H332	Harmful if inhaled.
		H315	Causes skin irritation.
		H319	Causes serious eye irritation.
		H335	May cause respiratory irritation.
		H373	May cause damage to organs through prolonged or repeated exposure.
16.6.	Training advice:		-
			** "X" in the product code marks different volumes (different packaging of the product)
16.7.	Further information:		We are not responsible for consequences in case of failure to comply with instructions for use or improper use of the product described in this material safety data sheet.
ΔΝΝΕ	EX. E	Exposure scenario	o resulting to Chemical safety assessment